



AiP74LV48751

1-of-8 Analog Multiplexer/Demultiplexer

Product Specification

Specification Revision History:

Version	Date	Description
2025-03-A0	2025-03	New
2025-05-A1	2025-05	Modify the parameters



Contents

1、General Description.....	3
2、Block Diagram And Pin Description	4
2.1、Block Diagram	4
2.2、Pin Configurations.....	5
2.3、Pin Description.....	5
2.4、Function Table.....	6
3、Electrical Parameter	6
3.1、Absolute Maximum Ratings.....	6
3.2、Recommended Operating Conditions.....	6
3.3、Electrical Characteristics.....	7
3.3.1、DC Characteristics 1	7
3.3.2、DC Characteristics 2.....	8
3.3.3、AC Characteristics 1.....	10
3.3.4、AC Characteristics 2.....	11
3.3.5、AC Characteristics 3.....	12
4、Testing Circuit	13
4.1、AC Testing Circuit 1	13
4.2、AC Testing Waveforms.....	13
4.3、AC Testing Circuit 2	14
4.4、On Resistance Test Circuit.....	18
4.5、DC Testing Circuit	18
4.6、Measurement Points	19
4.7、Test Data	19
5、Package Information	20
5.1、SOP16	20
5.2、SSOP16.....	21
5.3、TSSOP16.....	22
5.4、QFN16.....	23
6、Statements And Notes	24
6.1、The name and content of Hazardous substances or Elements in the product	24
6.2、Notes	24



1、General Description

The AiP74LV48751 is an 8-channel analog multiplexer/demultiplexer with three digital select inputs (S0 to S2), an active-LOW enable input (E), eight independent inputs/outputs (Y0 to Y7) and a common input/output (Z).

Features:

- Optimized for low-voltage applications: 2.0V to 6.0V
- Accepts TTL input levels between $V_{CC}=2.7V$ and $V_{CC}=3.6V$
- Low ON resistance:
 - 110 Ω (typical) at $V_{CC}=2.0V$
 - 90 Ω (typical) at $V_{CC}=3.0V$
 - 60 Ω (typical) at $V_{CC}=4.5V$
- Logic level translation: to enable 3V logic to communicate with $\pm 3V$ analog signals
- Typical 'break before make' built in
- Specified from -40 $^{\circ}C$ to +125 $^{\circ}C$
- Packaging information: SOP16/SSOP16/TSSOP16/QFN16

Ordering Information:

Reel packing specifications:

Part number	Packaging form	Marking code	Reel quantity	Boxed reel quantity	Notes
AiP74LV48751SA16.TR	SOP16	74LV48751	4000 PCS/reel	8000 PCS/box	Dimensions of plastic enclosure: 10.0mm×3.9mm Pin spacing: 1.27mm
AiP74LV48751VB16.TR	SSOP16	74LV48751	4000 PCS/reel	8000 PCS/box	Dimensions of plastic enclosure: 4.9mm×3.9mm Pin spacing: 0.635mm
AiP74LV48751TA16.TR	TSSOP16	74LV48751	5000 PCS/reel	10000 PCS/box	Dimensions of plastic enclosure: 5.0mm×4.4mm Pin spacing: 0.65mm
AiP74LV48751QA16.TR	QFN16	74LV48751	6000 PCS/reel	12000 PCS/box	Dimensions of plastic enclosure: 3.0mm×3.0mm Pin spacing: 0.5mm

Note: If the physical information is inconsistent with the ordering information, please refer to the actual product.



2、Block Diagram And Pin Description

2.1、Block Diagram




Figure 1. Functional diagram





Figure 2. Schematic diagram (one switch)



2.2、Pin Configurations



2.3、Pin Description

Pin No.		Pin Name	Description
SOP16/SSOP16/TSSOP16	QFN16		
1	15	Y4	independent input or output
2	16	Y6	independent input or output
3	1	Z	common output or input
4	2	Y7	independent input or output
5	3	Y5	independent input or output
6	4	$\bar{E}$	enable input (active LOW)
7	5	NC	not connect
8	6	GND	ground (0V)
9	7	S2	select input
10	8	S1	select input
11	9	S0	select input
12	10	Y3	independent input or output
13	11	Y0	independent input or output
14	12	Y1	independent input or output
15	13	Y2	independent input or output
16	14	V _{CC}	supply voltage



2.4、Function Table

Input				Channel ON
$\bar{E}$	S2	S1	S0	
L	L	L	L	Y0 to Z
L	L	L	H	Y1 to Z
L	L	H	L	Y2 to Z
L	L	H	H	Y3 to Z
L	H	L	L	Y4 to Z
L	H	L	H	Y5 to Z
L	H	H	L	Y6 to Z
L	H	H	H	Y7 to Z
H	X	X	X	switches off

Note: H=HIGH voltage level; L=LOW voltage level; X=don't care.

3、Electrical Parameter

3.1、Absolute Maximum Ratings

(Voltages are referenced to GND (ground=0V), unless otherwise specified.)

Parameter	Symbol	Conditions	Min.	Max.	Unit
supply voltage	V_{CC}	-	-0.5	+7.0	V
input clamping current	I_{IK}	$V_I < -0.5V$ or $V_I > V_{CC} + 0.5V$	-	± 20	mA
switch clamping current	I_{SK}	$V_{SW} < -0.5V$ or $V_{SW} > V_{CC} + 0.5V$	-	± 20	mA
switch current	I_{SW}	$V_{SW} > -0.5V$ or $V_{SW} < V_{CC} + 0.5V$; source or sink current	-	± 25	mA
storage temperature	T_{stg}	-	-65	+150	°C
total power dissipation	P_{tot}	-	-	500	mW
soldering temperature	T_L	10s	260		°C

3.2、Recommended Operating Conditions

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
supply voltage	V_{CC}	-	2	3.3	6	V
input voltage	V_I	-	0	-	V_{CC}	V
switch voltage	V_{SW}	-	0	-	V_{CC}	V
ambient temperature	T_{amb}	in free air	-40	-	+125	°C
input transition rise and fall rate	$\Delta t / \Delta V$	$V_{CC} = 2.0V$ to $2.7V$	-	-	200	ns/V
		$V_{CC} = 2.7V$ to $6.0V$	-	-	100	ns/V



3.3、Electrical Characteristics

3.3.1、DC Characteristics 1

($T_{amb} = -40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified.)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
HIGH-level input voltage	V_{IH}	$V_{CC}=2.0\text{V}$		1.4	-	-	V
		$V_{CC}=2.7\text{V to }3.6\text{V}$		2.0	-	-	V
		$V_{CC}=4.5\text{V}$		3.15	-	-	V
		$V_{CC}=6.0\text{V}$		4.20	-	-	V
LOW-level input voltage	V_{IL}	$V_{CC}=2.0\text{V}$		-	-	0.5	V
		$V_{CC}=2.7\text{V to }3.6\text{V}$		-	-	0.7	V
		$V_{CC}=4.5\text{V}$		-	-	1.15	V
		$V_{CC}=6.0\text{V}$		-	-	1.60	V
input leakage current	I_I	$V_I = V_{CC}$ or GND	$V_{CC}=3.6\text{V}$	-	-	1.0	μA
			$V_{CC}=6.0\text{V}$	-	-	2.0	μA
OFF-state leakage current	$I_{S(OFF)}$	$V_I = V_{IH}$ or V_{IL} ; see Figure 12	$V_{CC}=3.6\text{V}$	-	-	1.0	μA
			$V_{CC}=6.0\text{V}$	-	-	2.0	μA
ON-state leakage current	$I_{S(ON)}$	$V_I = V_{IH}$ or V_{IL} ; see Figure 13	$V_{CC}=3.6\text{V}$	-	-	1.0	μA
			$V_{CC}=6.0\text{V}$	-	-	2.0	μA
supply current	I_{CC}	$V_I = V_{CC}$ or GND; $I_O=0\text{A}$	$V_{CC}=3.6\text{V}$	-	-	20	μA
			$V_{CC}=6.0\text{V}$	-	-	40	μA
additional supply current	ΔI_{CC}	per input; $V_I = V_{CC}-0.6\text{V}$; $V_{CC}=2.7\text{V to }3.6\text{V}$		-	-	500	μA
ON resistance (peak)	$R_{ON(peak)}$	$V_I=0\text{V to }V_{CC}$	$V_{CC}=2.0\text{V}$; $I_{SW}=1000\mu\text{A}$	-	290	650	Ω
			$V_{CC}=2.7\text{V}$; $I_{SW}=1000\mu\text{A}$	-	150	300	Ω
			$V_{CC}=3.0\text{V to }3.6\text{V}$; $I_{SW}=1000\mu\text{A}$	-	100	200	Ω
			$V_{CC}=4.5\text{V}$; $I_{SW}=1000\mu\text{A}$	-	80	160	Ω
			$V_{CC}=6.0\text{V}$; $I_{SW}=1000\mu\text{A}$	-	65	130	Ω
ON resistance mismatch between channels	ΔR_{ON}	$V_I=0\text{V to }V_{CC}$	$V_{CC}=2.0\text{V}$; $I_{SW}=1000\mu\text{A}$	-	5	-	Ω
			$V_{CC}=2.7\text{V}$; $I_{SW}=1000\mu\text{A}$	-	4	-	Ω
			$V_{CC}=3.0\text{V to }3.6\text{V}$; $I_{SW}=1000\mu\text{A}$	-	4	-	Ω
			$V_{CC}=4.5\text{V}$; $I_{SW}=1000\mu\text{A}$	-	3	-	Ω
			$V_{CC}=6.0\text{V}$; $I_{SW}=1000\mu\text{A}$	-	2	-	Ω
ON resistance (rail)	$R_{ON(rail)}$	$V_I=\text{GND}$	$V_{CC}=2.0\text{V}$; $I_{SW}=1000\mu\text{A}$	-	110	235	Ω



			$V_{CC}=2.7V$; $I_{SW}=1000uA$	-	85	170	Ω
			$V_{CC}=3.0V$ to $3.6V$; $I_{SW}=1000uA$	-	65	130	Ω
			$V_{CC}=4.5V$; $I_{SW}=1000uA$	-	60	120	Ω
			$V_{CC}=6.0V$; $I_{SW}=1000uA$	-	50	100	Ω
		$V_I=V_{CC}$	$V_{CC}=2.0V$; $I_{SW}=1000uA$	-	150	320	Ω
			$V_{CC}=2.7V$; $I_{SW}=1000uA$	-	110	220	Ω
			$V_{CC}=3.0V$ to $3.6V$; $I_{SW}=1000uA$	-	85	170	Ω
			$V_{CC}=4.5V$; $I_{SW}=1000uA$	-	70	140	Ω
			$V_{CC}=6.0V$; $I_{SW}=1000uA$	-	60	120	Ω

Note:

[1] Typical values are measured at $T_{amb}=25^{\circ}C$.

3.3.2、DC Characteristics 2

(T_{amb}=-40°C to +125°C, voltages are referenced to GND (ground=0V), unless otherwise specified.)

Parameter	Symbol	Conditions (V)		Min.	Typ.	Max.	Unit
HIGH-level input voltage	V_{IH}	$V_{CC}=2.0V$		1.4	-	-	V
		$V_{CC}=2.7V$ to $3.6V$		2.0	-	-	V
		$V_{CC}=4.5V$		3.15	-	-	V
		$V_{CC}=6.0V$		4.20	-	-	V
LOW-level input voltage	V_{IL}	$V_{CC}=2.0V$		-	-	0.5	V
		$V_{CC}=2.7V$ to $3.6V$		-	-	0.7	V
		$V_{CC}=4.5V$		-	-	1.15	V
		$V_{CC}=6.0V$		-	-	1.60	V
input leakage current	I_I	$V_I=V_{CC}$ or GND	$V_{CC}=3.6V$	-	-	2.0	μA
			$V_{CC}=6.0V$	-	-	4.0	μA
OFF-state leakage current	$I_{S(OFF)}$	$V_I=V_{IH}$ or V_{IL} ; see Figure 12	$V_{CC}=3.6V$	-	-	2.0	μA
			$V_{CC}=6.0V$	-	-	4.0	μA
ON-state leakage current	$I_{S(ON)}$	$V_I=V_{IH}$ or V_{IL} ; see Figure 13	$V_{CC}=3.6V$	-	-	2.0	μA
			$V_{CC}=6.0V$	-	-	4.0	μA
supply current	I_{CC}	$V_I=V_{CC}$ or GND; $I_O=0A$	$V_{CC}=3.6V$	-	-	40	μA
			$V_{CC}=6.0V$	-	-	80	μA
additional supply current	ΔI_{CC}	per input; $V_I=V_{CC}-0.6V$; $V_{CC}=2.7V$ to $3.6V$		-	-	850	μA
ON resistance (peak)	$R_{ON(peak)}$	$V_I=0V$ to V_{CC}	$V_{CC}=2.0V$; $I_{SW}=1000uA$	-	-	750	Ω



			$V_{CC}=2.7V$; $I_{SW}=1000\mu A$	-	-	350	Ω
			$V_{CC}=3.0V$ to $3.6V$; $I_{SW}=1000\mu A$	-	-	250	Ω
			$V_{CC}=4.5V$; $I_{SW}=1000\mu A$	-	-	200	Ω
			$V_{CC}=6.0V$; $I_{SW}=1000\mu A$	-	-	150	Ω
ON resistance (rail)	$R_{ON(rail)}$	$V_I=GND$	$V_{CC}=2.0V$; $I_{SW}=1000\mu A$	-	-	270	Ω
			$V_{CC}=2.7V$; $I_{SW}=1000\mu A$	-	-	200	Ω
			$V_{CC}=3.0V$ to $3.6V$; $I_{SW}=1000\mu A$	-	-	150	Ω
			$V_{CC}=4.5V$; $I_{SW}=1000\mu A$	-	-	140	Ω
			$V_{CC}=6.0V$; $I_{SW}=1000\mu A$	-	-	120	Ω
		$V_I=V_{CC}$	$V_{CC}=2.0V$; $I_{SW}=1000\mu A$	-	-	370	Ω
			$V_{CC}=2.7V$; $I_{SW}=1000\mu A$	-	-	250	Ω
			$V_{CC}=3.0V$ to $3.6V$; $I_{SW}=1000\mu A$	-	-	205	Ω
			$V_{CC}=4.5V$; $I_{SW}=1000\mu A$	-	-	150	Ω
			$V_{CC}=6.0V$; $I_{SW}=1000\mu A$	-	-	135	Ω

Note:

[1] Typical values are measured at $T_{amb}=25^{\circ}C$.



3.3.3、AC Characteristics 1

($T_{amb} = -40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified.)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
propagation delay	t_{pd}	Yn to Z, Z to Yn; see Figure 4	$V_{CC}=2.0V$	-	9	17	ns
			$V_{CC}=2.7V$	-	6	13	ns
			$V_{CC}=3.0V$ to $3.6V$	-	5	10	ns
			$V_{CC}=4.5V$	-	4	9	ns
			$V_{CC}=6.0V$	-	3	8	ns
enable time	t_{en}	$\overline{E}$ to Yn, Z; see Figure 5	$V_{CC}=2.0V$	-	49	94	ns
			$V_{CC}=2.7V$	-	36	69	ns
			$V_{CC}=3.0V$ to $3.6V$; $C_L=15pF$	-	23	-	ns
			$V_{CC}=3.0V$ to $3.6V$	-	28	55	ns
			$V_{CC}=4.5V$	-	25	47	ns
			$V_{CC}=6.0V$	-	19	38	ns
		Sn to Yn ,see Figure 5	$V_{CC}=2.0V$	-	48	90	ns
			$V_{CC}=2.7V$	-	35	66	ns
			$V_{CC}=3.0V$ to $3.6V$; $C_L=15pF$	-	22	-	ns
			$V_{CC}=3.0V$ to $3.6V$	-	27	53	ns
			$V_{CC}=4.5V$	-	24	45	ns
			$V_{CC}=6.0V$	-	18	34	ns
disable time	t_{dis}	$\overline{E}$ to Yn; see Figure 5	$V_{CC}=2.0V$	-	51	93	ns
			$V_{CC}=2.7V$	-	38	69	ns
			$V_{CC}=3.0V$ to $3.6V$; $C_L=15pF$	-	25	-	ns
			$V_{CC}=3.0V$ to $3.6V$	-	30	56	ns
			$V_{CC}=4.5V$	-	29	48	ns
			$V_{CC}=6.0V$	-	21	37	ns
		Sn to Yn; see Figure 5	$V_{CC}=2.0V$	-	41	73	ns
			$V_{CC}=2.7V$	-	31	54	ns
			$V_{CC}=3.0V$ to $3.6V$; $C_L=15pF$	-	20	-	ns
			$V_{CC}=3.0V$ to $3.6V$	-	24	44	ns
			$V_{CC}=4.5V$	-	22	37	ns
			$V_{CC}=6.0V$	-	17	29	ns

Note:

[1] Typical values are measured at $T_{amb}=25^{\circ}\text{C}$.

[2] t_{pd} is the same as t_{PLH} and t_{PHL} .

t_{en} is the same as t_{PZL} and t_{PZH} .

t_{dis} is the same as t_{PLZ} and t_{PHZ} .

[3] Typical values are measured at nominal supply voltage ($V_{CC}=3.3\text{V}$).



3.3.4、AC Characteristics 2

($T_{amb} = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified.)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
propagation delay	t_{pd}	Yn to Z, Z to Yn; see Figure 4	$V_{CC}=2.0V$	-	-	20	ns
			$V_{CC}=2.7V$	-	-	15	ns
			$V_{CC}=3.0V$ to $3.6V$	-	-	12	ns
			$V_{CC}=4.5V$	-	-	10	ns
			$V_{CC}=6.0V$	-	-	8	ns
enable time	t_{en}	$\overline{E}$ to Yn, Z; see Figure 5	$V_{CC}=2.0V$	-	-	112	ns
			$V_{CC}=2.7V$	-	-	83	ns
			$V_{CC}=3.0V$ to $3.6V$	-	-	66	ns
			$V_{CC}=4.5V$	-	-	56	ns
			$V_{CC}=6.0V$	-	-	43	ns
		Sn to Yn; see Figure 5	$V_{CC}=2.0V$	-	-	107	ns
			$V_{CC}=2.7V$	-	-	79	ns
			$V_{CC}=3.0V$ to $3.6V$	-	-	63	ns
			$V_{CC}=4.5V$	-	-	54	ns
			$V_{CC}=6.0V$	-	-	41	ns
disable time	t_{dis}	$\overline{E}$ to Yn, Z; see Figure 5	$V_{CC}=2.0V$	-	-	110	ns
			$V_{CC}=2.7V$	-	-	82	ns
			$V_{CC}=3.0V$ to $3.6V$	-	-	66	ns
			$V_{CC}=4.5V$	-	-	56	ns
			$V_{CC}=6.0V$	-	-	44	ns
		Sn to Yn; see Figure 5	$V_{CC}=2.0V$	-	-	90	ns
			$V_{CC}=2.7V$	-	-	67	ns
			$V_{CC}=3.0V$ to $3.6V$	-	-	54	ns
			$V_{CC}=4.5V$	-	-	46	ns
			$V_{CC}=6.0V$	-	-	36	ns

Note:

[1] t_{pd} is the same as t_{PLH} and t_{PHL} .

t_{en} is the same as t_{PZL} and t_{PZH} .

t_{dis} is the same as t_{PLZ} and t_{PHZ} .



3.3.5、AC Characteristics 3

($T_{amb}=25^{\circ}\text{C}$, $GND=0V$, $t_r=t_f\leq 6.0\text{ns}$, $V_I=GND$ or V_{CC} , unless otherwise specified.)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
total harmonic distortion	THD	f_i =1kHz; C_L =50pF; R_L =10k Ω ; see Figure 8	V_{CC} =3.0V; V_I =2.75V(p-p)	-	0.8	-	%
			V_{CC} =6.0V; V_I =5.5V(p-p)	-	0.4	-	%
		f_i =10kHz; C_L =50pF; R_L =10k Ω ; see Figure 8	V_{CC} =3.0V; V_I =2.75V(p-p)	-	2.4	-	%
			V_{CC} =6.0V; V_I =5.5V(p-p)	-	1.2	-	%
-3dB frequency response	$f_{(-3dB)}$	C_L =50pF; R_L =50 Ω ; see Figure 6	V_{CC} =3.0V	-	180	-	MHz
			V_{CC} =6.0V	-	200	-	MHz
isolation (OFF-state)	α_{iso}	f_i =1MHz; C_L =50pF; R_L =600 Ω ; see Figure 7	V_{CC} =3.0V	-	-50	-	dB
			V_{CC} =6.0V	-	-50	-	dB
crosstalk voltage	V_{ct}	between digital inputs and switch; f_i =1MHz; C_L =50pF; R_L =600 Ω ; see Figure 9	V_{CC} =3.0V	-	0.11	-	V
			V_{CC} =6.0V	-	0.12	-	V
crosstalk	Xtalk	between switches; f_i =1MHz; C_L =50pF; R_L =600 Ω ; see Figure 10	V_{CC} =3.0V	-	-60	-	dB
			V_{CC} =6.0V	-	-60	-	dB

Note:

[1] To obtain 0dBm level at output for 1MHz (0dBm=1mW into 50 Ω), adjust f_i voltage.

[2] To obtain 0dBm level at output for 1MHz (0dBm=1mW into 600 Ω), adjust f_i voltage.



4、Testing Circuit

4.1、AC Testing Circuit 1




Figure 3. Test circuit for switching times

Definitions for test circuit:

C_L =Load capacitance including jig and probe capacitance.

R_T =Termination resistance should be equal to the output impedance Z_o of the pulse generator.

R_L =Load resistance.

V_{EXT} =External voltage for measuring switching times.

4.2、AC Testing Waveforms




Figure 4. Yn to Z, Z to Yn propagation delays




Figure 5. Enable and disable times

4.3、AC Testing Circuit 2




Figure 6. Test circuit for measuring frequency response




Figure 7. Test circuit for measuring isolation (OFF-state)






Figure 8. Test circuit for measuring total harmonic distortion




a. Test circuit




b. Input and output pulse definitions

V_I may be connected to S_n or $\bar{E}$.

Figure 9. Test circuit for measuring crosstalk voltage between digital inputs and switch



a. Switch closed condition.




b. Switch open condition

Figure 10. Test circuit for measuring crosstalk between switches




4.4、On Resistance Test Circuit



$$R_{ON} = V_{SW} / I_{SW}$$


Figure 11. Test circuit for measuring R_{ON}

4.5、DC Testing Circuit



$$V_I = V_{CC} \text{ and } V_O = V_{CC}$$

Figure 12. Test circuit for measuring OFF-state leakage current



$V_I = V_{CC}$ and $V_O = \text{open circuit}$

Figure 13. Test circuit for measuring ON-state leakage current

4.6、Measurement Points

Supply voltage	Input	Output		
V_{CC}	V_M	V_M	V_X	V_Y
$<2.7V$	$0.5 \times V_{CC}$	$0.5 \times V_{CC}$	$0.1V_{CC}$	$V_O - 0.1V_{CC}$
2.7V to 3.6V	1.5V	1.5V	0.3V	$V_O - 0.3V$
$>3.6V$	$0.5 \times V_{CC}$	$0.5 \times V_{CC}$	$0.1V_{CC}$	$V_O - 0.1V_{CC}$



4.7、Test Data

Supply voltage	Input		Load		V_{EXT}		
V_{CC}	V_I	t_r, t_f	C_L	R_L	t_{PHL}, t_{PLH}	t_{PZH}, t_{PHZ}	t_{PZL}, t_{PLZ}
$<2.7V$	V_{CC}	$\leq 6ns$	50pF	1k Ω	open	GND	$2 \times V_{CC}$
2.7V to 3.6V	2.7V	$\leq 6ns$	15 pF, 50pF	1k Ω	open	GND	$2 \times V_{CC}$
$>3.6V$	V_{CC}	$\leq 6ns$	50pF	1k Ω	open	GND	$2 \times V_{CC}$



5、Package Information


5.1、SOP16



2023/12/A	Dimensions In Millimeters	
Symbol	Min.	Max.
A	1.35	1.80
A1	0.10	0.25
A2	1.25	1.55
b	0.33	0.51
c	0.19	0.25
D	9.50	10.10
E	5.80	6.30
E1	3.70	4.10
e	1.27	
L	0.35	0.89
θ	0°	8°






5.2、SSOP16



2023/12/A	Dimensions In Millimeters	
Symbol	Min	Max
A	—	1.75
A1	0.02	0.23
A2	1.30	1.50
b	0.23	0.31
c	0.20	0.24
D	4.70	5.10
E	5.80	6.25
E1	3.80	4.02
e	0.635	
L	0.45	0.80
L1	1.05	
θ	0°	8°




5.3、TSSOP16



2023/12/A	Dimensions In Millimeters	
Symbol	Min	Max
A	—	1.20
A1	0.05	0.15
A2	0.80	1.05
b	0.19	0.30
c	0.09	0.20
D	4.90	5.10
E1	4.30	4.50
E	6.20	6.60
e	0.65	
L	0.45	0.75
θ	0°	8°



5.4、QFN16



2024/01/B	Dimensions In Millimeters	
Symbol	Min	Max
A	0.70	0.80
A1	0	0.05
b	0.18	0.30
b1	0.16	
c	0.18	0.25
D	2.90	3.10
D2	1.55	1.80
e	0.50	
Ne	1.50	
Nd	1.50	
E	2.90	3.10
E2	1.55	1.80
L	0.30	0.50
h	0.20	0.45



6、Statements And Notes

6.1、The name and content of Hazardous substances or Elements in the product

Part name	Hazardous substances or Elements									
	Lead and lead compounds	Mercury and mercury compounds	Cadmium and cadmium compounds	Hexavalent chromium compounds	Polybrominated biphenyls	Polybrominated biphenyl ethers	Dibutyl phthalate	Butylbenzyl phthalate	Di-2-ethylhexyl phthalate	Diisobutyl phthalate
Lead frame	○	○	○	○	○	○	○	○	○	○
Plastic resin	○	○	○	○	○	○	○	○	○	○
Chip	○	○	○	○	○	○	○	○	○	○
The lead	○	○	○	○	○	○	○	○	○	○
Plastic sheet installed	○	○	○	○	○	○	○	○	○	○
explanation	○: Indicates that the content of hazardous substances or elements in the detection limit of the following the SJ/T11363-2006 standard. ×: Indicates that the content of hazardous substances or elements exceeding the SJ/T11363-2006 Standard limit requirements.									

6.2、Notes

We recommend you to read this chapter carefully before using this product.

The information in this chapter is provided for reference only and i-Core disclaims any express or implied warranties, including but not limited to applicability, special application or non-infringement of third party rights.

This product is not suitable for critical equipment such as life-saving, life-sustaining or safety equipment. It is also not suitable for applications that may result in personal injury, death, or serious property or environmental damage due to product malfunction or failure. I-Core will not be liable for any damages incurred by the customers at their own risk for such applications.

The customer is responsible for conducting all necessary tests i-Core's application to avoid failure in the application or the application of the customer's third party users. I-Core does not accept any liability.

The Company reserves the right to change or improve the information published in this chapter at any time. The information in this chapter are subject to change without notice. We recommend the customer to consult our sales staff before purchasing.

Please obtain related materials from i-Core's regular channels and we are not responsible for its content if it is provided by sources other than our company.

In case of any conflict between the Chinese and English version, the version is subject to the Chinese one.